GN 2295-elongated

Hinges

for aluminum profiles / panel elements, three-part, vertically elongated outer wings

SPECIFICATION

Types

10

11

14

15

16

Hinges and accessories 12

- Type A: exterior hinge wings
- Type I: interior hinge wings

Identification no.

No. C: with countersunk holes

Aluminum EL anodized, natural color

Bearing bushing / cover cap

- Plastic, Technopolymer (Polyamide PA) - Graphite gray, RAL 7024

Tapered dowel pin ISO 8741 Steel zinc plated, blue passivated

INFORMATION

GN 2295 Hinges are made of drawn profiled aluminum and are used on doors and covers, for example.

Given the external hinge wing, type A hinges allow mounting with a very small door gap. The type I is fastened in the door gap. The mounting screws are therefore inaccessible and hence protected from vandalism when the door is closed.

The hinges are delivered loose and must be mounted according to the accompanying instructions. Any hinge combination may be realized (if needed, also by shortening the middle wing) thanks to the modular design and available accessories.


TECHNICAL INFORMATION

- Plastic characteristics (see page A2)

ON REQUEST

- other lengths and hole spacings


- other finishes



 d_2

Bore for counter-

sunk head screw DIN 7991



Assembly instruction





GN 2295-elongated

Description	11	12	14	d 1	d2	13	15	16	m1	m2	m3	m4	m5	m6	s	52
GN 2295-72-245-A-C-EL	72	245	80	6.6	14	80	36	-	40.8	50	32.5	50	-	-	3.5	168
GN 2295-86-245-I-C-EL	86	245	80	6.6	14	80	-	43	55	50	32.5	50	-	-	3.5	177
GN 2295-72-415-A-C-EL	72	415	250	6.6	14	80	36	-	40.8	-	-	-	67.5	150	3.5	267
GN 2295-86-415-I-C-EL	86	415	250	6.6	14	80	-	43	55	-	-	-	67.5	150	3.5	282
GN 2295-72-565-A-C-EL	72	565	400	6.6	14	80	36	-	40.8	-	-	-	67.5	150	3.5	353
GN 2295-86-565-I-C-EL	86	565	400	6.6	14	80	-	43	55	-	-	-	67.5	150	3.5	375

Type

С





۲

7/2023

