



Cabinet U-Handles

Aluminum

SPECIFICATION

Aluminum AL

Powder coated, textured finish Black, RAL 9005 **SW** Silver, RAL 9006 **SR**

Powder coated, antimicrobial finish

Black, RAL 9005 **SMA** White, RAL 9016 **WSA** Plain, tumbled **BL**



Cabinet U-handles GN 426 are manufactured from a bent aluminum profile and have excellent stability and ergonomic design.


In addition to the standard surfaces, these cabinet U-handles are also available with a functional coating.


The **SMA / WSA** versions have a powder coating based on silver ions, which gives them antimicrobial properties. The principle of action has been shown to reduce the contamination of the handle surfaces within 24 hours so that fewer than 1% of bacteria and fewer than 5% of viruses ultimately survive.

Standard parts with antimicrobial plastic coating are primarily used in the health care sector and in public buildings, such as airports, train stations, stadiums, etc.

TECHNICAL INFORMATION

- Load Rating Information (see page A35)







RAL 9005 RAL 9006 RAL 9005, antimicrobial RAL 9016, antimicrobial Plain, tumbled

GN 426

Description	d 1	I ±0.25	d ₂	h	r	t min.	2.7
GN 426-AL-20-200-*	20	200	M 8	68	22	15	250
GN 426-AL-20-250-*	20	250	M 8	68	22	15	280
GN 426-AL-20-300-*	20	300	M 8	68	22	15	330
GN 426-AL-20-350-*	20	350**	M 8	68	22	15	370
GN 426-AL-28-250-*	28	250	M 10	78	32	15	550
GN 426-AL-28-300-*	28	300	M 10	78	32	15	639
GN 426-AL-28-350-*	28	350**	M 10	78	32	15	719
GN 426-AL-28-400-*	28	400	M 10	78	32	15	776

^{**} Not available for WSA, SMA

