

Threaded Plugs

Aluminum, with Wing Knob, up to 200°C

SPECIFICATION

Identification no.

- No. **1**: without vent hole
- No. **2**: with vent hole

Aluminium

plastic coated

black, RAL 9005, matte finish **SW**

blank, ground **BL**

temperature resistant up to **200 °C**

Sealing ring rubber FPM (Viton®)

Identification by not black finish of the seal



INFORMATION

Threaded plugs GN 442 with the external diameter d_1 match the screw-in holes for DIN 3852 pipe bolt connections.


The sealing ring is embedded in a radial recess on the plane side, which makes the sealing ring captive and cannot be squeezed out during tightening. The sealing is also relatively soft, enhancing the sealing effect also on uneven surfaces.

ON REQUEST

- Threaded plugs with dipstick

TECHNICAL INFORMATION

- Elastomer characteristics (see page A32)



* Complete with colour index of the Threaded plugs

SW **BL**
RAL9005 blank

GN 442

Description	d1	d2	d3	d4	l1 ±0.5	l2	l3	s	t min.	⚙
GN 442-22-M16x1,5-1-*	22	M 16 x 1.5	-	M 5	26	8	15	5	8	12
GN 442-22-M16x1,5-2-*	22	M 16 x 1.5	2	M 5	26	8	15	5	8	12
GN 442-26-M20x1,5-1-*	26	M 20 x 1.5	-	M 5	27.5	8.5	16	5	8	17
GN 442-26-M20x1,5-2-*	26	M 20 x 1.5	2	M 5	27.5	8.5	16	5	8	17
GN 442-32-M26x1,5-1-*	32	M 26 x 1.5	-	M 5	29	9	17	6	8	27
GN 442-32-M26x1,5-2-*	32	M 26 x 1.5	2	M 5	29	9	17	6	8	27
GN 442-22-G3/8-1-*	22	G 3/8	-	M 5	26	8	15	5	8	12
GN 442-22-G3/8-2-*	22	G 3/8	2	M 5	26	8	15	5	8	12
GN 442-26-G1/2-1-*	26	G 1/2	-	M 5	27.5	8.5	16	5	8	17
GN 442-26-G1/2-2-*	26	G 1/2	2	M 5	27.5	8.5	16	5	8	17
GN 442-32-G3/4-1-*	32	G 3/4	-	M 5	29	9	17	6	8	27
GN 442-32-G3/4-2-*	32	G 3/4	2	M 5	29	9	17	6	8	27
GN 442-40-G1-1-*	40	G 1	-	M 5	32.5	11	18	7	8	48
GN 442-40-G1-2-*	40	G 1	2	M 5	32.5	11	18	7	8	48

Weight colour SW