

Knurled Screws

Steel / Stainless Steel

SPECIFICATION

Stainless Steel AISI 304




- matt shot-blasted **MT**
- highly polished **PL**

INFORMATION

The knurling of Stainless Steel-Knurled screws GN 535 allows a use in an environment with hygienic requirements.

TECHNICAL INFORMATION

- Stainless Steel characteristics (see page A26)



Knurled Nuts

Stainless Steel

SPECIFICATION

Stainless Steel AISI 304




- matt shot-blasted **MT**
- highly polished **PL**

INFORMATION

The knurling of Stainless Steel-Knurled nuts GN 536 allows a use in an environment with hygienic requirements.

TECHNICAL INFORMATION

- Stainless Steel characteristics (see page A26)



GN 535

STAINLESS STEEL

Description	d1	d2	l	d3	h	k	⚖
GN 535-20-M5-10-MT	20	M 5	10	14	13	8.5	26
GN 535-20-M5-10-PL	20	M 5	10	14	13	8.5	26
GN 535-20-M5-16-MT	20	M 5	16	14	13	8.5	27
GN 535-20-M5-16-PL	20	M 5	16	14	13	8.5	27
GN 535-24-M6-16-MT	24	M 6	16	16	15	10.5	43
GN 535-24-M6-16-PL	24	M 6	16	16	15	10.5	43
GN 535-24-M6-20-MT	24	M 6	20	16	15	10.5	44
GN 535-24-M6-20-PL	24	M 6	20	16	15	10.5	44
GN 535-24-M6-25-MT	24	M 6	25	16	15	10.5	45
GN 535-24-M6-25-PL	24	M 6	25	16	15	10.5	45
GN 535-28-M8-16-MT	28	M 8	16	18	17	12.5	68
GN 535-28-M8-16-PL	28	M 8	16	18	17	12.5	68
GN 535-28-M8-20-MT	28	M 8	20	18	17	12.5	69
GN 535-28-M8-20-PL	28	M 8	20	18	17	12.5	69
GN 535-28-M8-30-MT	28	M 8	30	18	17	12.5	72
GN 535-28-M8-30-PL	28	M 8	30	18	17	12.5	72

GN 536

STAINLESS STEEL

Description	d1	d2	d3	h	k	t min.	⚖
GN 536-20-M5-MT	20	M 5	14	13	8.5	8	24
GN 536-20-M5-PL	20	M 5	14	13	8.5	8	24
GN 536-24-M6-MT	24	M 6	16	15	10.5	9	38
GN 536-24-M6-PL	24	M 6	16	15	10.5	9	38
GN 536-28-M8-MT	28	M 8	18	17	12.5	10	58
GN 536-28-M8-PL	28	M 8	18	17	12.5	10	58