

System handles

Aluminium

SPECIFICATION

Types

- Type **A**: Mounting from the back (threaded blind bore)
- Type **B**: Mounting from the operator's side

Tube / End pieces

Aluminium

plastic coated

black, RAL 9005, textured finish **SW**

anodized, natural colour **EL**

Cover caps

Plastic

Technopolymer (Polyamide PA)

black, matt

Socket head screws DIN 912-M8x75

Steel, zinc plated

Hexagon nuts ISO 4032-M8

Steel, zinc plated

Washers DIN 125

Steel, zinc plated

INFORMATION

System handles GN 669 offer the the advantage of high stability due to the connection of tube / handle shank.
The screws of type B (mounting from operator's side) are shrouded.

TECHNICAL INFORMATION

- Load rating information (see page A35)

MOUNTING INFORMATION

When mounting from the operator's side (Type B) the plastic end covers are supplied loose. Once the handle has been-mounted the end covers are pushed over the end of the handle tube and the foot until they snap into the end of the groove at the tube end.

Both mounting methods (Type A and B) allow the mounting of a pair of handles in opposite position. This method could be used on doors (double handle). Depending on the door thickness longer socket head screws DIN 912 might be required.

* Complete with colour index of the System handles (SW or EL)

SW **EL**
RAL9005 anodized

GN 669

Description	d1	l1 ±0.5	b	d2	h ≈	l2	l3 max.	l4	t min.	⚖
GN 669-28-200-A-*	28	200	32	M 8	60	20	11	-	15	180
GN 669-28-250-A-*	28	250	32	M 8	60	20	11	-	15	208
GN 669-28-300-A-*	28	300	32	M 8	60	20	11	-	15	220
GN 669-28-400-A-*	28	400	32	M 8	60	20	11	-	15	260
GN 669-28-500-A-*	28	500	32	M 8	60	20	11	-	15	290
GN 669-28-600-A-*	28	600	32	M 8	60	20	11	-	15	330
GN 669-28-200-B-*	28	200	32	M 8	60	20	11	20	-	245
GN 669-28-250-B-*	28	250	32	M 8	60	20	11	20	-	260
GN 669-28-300-B-*	28	300	32	M 8	60	20	11	20	-	275
GN 669-28-400-B-*	28	400	32	M 8	60	20	11	20	-	300
GN 669-28-500-B-*	28	500	32	M 8	60	20	11	20	-	350
GN 669-28-600-B-*	28	600	32	M 8	60	20	11	20	-	400

