

## Indexing plungers

Steel / Stainless Steel, with T-Handle, with and without rest position

### SPECIFICATION

#### Types

- Type **B**: without rest position, without lock nut
- Type **BK**: without rest position, with lock nut
- Type **C**: with rest position, without lock nut
- Type **CK**: with rest position, with lock nut

#### Version in Steel

- blackened
- Pin hardened and grounded

#### Version in Stainless Steel NI

- AISI 303
- Pin chemically nickel plated

T-Handle

Plastic Polyamide (PA)

- not removable
- black, matt

### INFORMATION

Indexing plungers GN 817.4 are similar to GN 817 (see page 754) but with a T-handle instead of a round head.

This shape allows better visual orientation of the indexing position of Type C and is advantageous when greater unlocking forces occur.

Type C with rest position is used in such applications where the plunger must not protrude continually. In that case the knob is retracted and afterwards turned by 90°. A notch keeps the plunger in this position.

- Range of indexing plungers (see page 738)

### TECHNICAL INFORMATION

- Stainless Steel characteristics (see page A26)

\* Complete with type index of the Indexing plungers (B, BK, C or CK)

B BK C CK

### GN 817.4

Description	d1 Pin -0.02/-0.05 Bore H7	l1	d2	k	l2	l3	l4	l5	A/F	Spring load in N ≈ initial	Spring load in N ≈ end	⚖
GN 817.4-6-6-*	6	6	M 12 x 1.5	20	48	22	6	54	14	6.5	19	31
GN 817.4-6-9-*	6	9	M 12 x 1.5	20	48	22	6	54	14	6	25	34
GN 817.4-8-8-*	8	8	M 16 x 1.5	25	59	26	8	59	17	8.5	26	64
GN 817.4-8-12-*	8	12	M 16 x 1.5	25	59	26	8	59	17	8.5	28	65
GN 817.4-10-12-*	10	12	M 16 x 1.5	25	59	26	8	59	17	9.5	38	72
GN 817.4-12-15-*	12	15	M 20 x 1.5	25	68	33	10	59	22	11.5	40	120

### GN 817.4-NI

STAINLESS STEEL

Description	d1 Pin -0.02/-0.05 Bore H7	l1	d2	k	l2	l3	l4	l5	A/F	Spring load in N ≈ initial	Spring load in N ≈ end	⚖
GN 817.4-6-6-*-NI	6	6	M 12 x 1.5	20	48	22	6	54	14	6.5	19	31
GN 817.4-6-9-*-NI	6	9	M 12 x 1.5	20	48	22	6	54	14	6	25	35
GN 817.4-8-8-*-NI	8	8	M 16 x 1.5	25	59	26	8	59	17	8.5	26	64
GN 817.4-8-12-*-NI	8	12	M 16 x 1.5	25	59	26	8	59	17	8.5	28	69
GN 817.4-10-12-*-NI	10	12	M 16 x 1.5	25	59	26	8	59	17	9.5	38	72
GN 817.4-12-15-*-NI	12	15	M 20 x 1.5	25	68	33	10	59	22	11.5	40	120

Weight type B

